

US008395555B2

(12) United States Patent

Hobson et al.

US 8,395,555 B2

*Mar. 12, 2013

(54) WIRELESS HANDHELD ELECTRONIC DEVICE

(75) Inventors: Phillip M. Hobson, Menlo Park, CA

(US); **Stephen P. Zadesky**, Portola Valley, CA (US); **Erik L. Wang**,

Redwood City, CA (US); Tang Yew Tan, San Francisco, CA (US); Richard Hung Minh Dinh, San Jose, CA (US); Adam D. Mittleman, San Francisco, CA (US); Kenneth A. Jenks, Cupertino, CA (US); Robert J. Hill, Salinas, CA (US); Robert W. Schlub, Campbell, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 13/008,586

(22) Filed: Jan. 18, 2011

(65) **Prior Publication Data**

US 2011/0109516 A1 May 12, 2011

Related U.S. Application Data

- (63) Continuation of application No. 12/142,552, filed on Jun. 19, 2008, now Pat. No. 7,876,274.
- (60) Provisional application No. 60/936,796, filed on Jun. 21, 2007.
- (51) **Int. Cl.**

H01Q 1/24 (2006.01)

U.S. Cl. 343/702; 343/846; 455/575.7

(56) References Cited

(10) Patent No.:

(45) **Date of Patent:**

U.S. PATENT DOCUMENTS

4,644,366 A * 4,723,305 A *	2/1987 2/1988	Scholz
4,894,663 A	1/1990	Urbish et al.
4,980,694 A	12/1990	Hines
5,021,010 A	6/1991	Wright
5,041,838 A	8/1991	Liimatainen et al.
5,048,118 A	9/1991	Brooks et al.
5,561,437 A	10/1996	Phillips et al.
5,754,143 A	5/1998	Warnagiris et al.
5,798,984 A	8/1998	Koch
6,011,699 A	1/2000	Murray et al.
6,031,503 A *	2/2000	Preiss et al 343/770
6,097,345 A	8/2000	Walton
(Continued)		

OTHER PUBLICATIONS

U.S. Appl. No. 60/883,587, filed Jan. 5, 2007, Hobson et al.

(Continued)

Primary Examiner — Michael C Wimer (74) Attorney, Agent, or Firm — Treyz Law Group; David C. Kellogg; G. Victor Treyz

(57) ABSTRACT

A handheld electronic device may be provided that contains a conductive housing and other conductive elements. The conductive elements may form an antenna ground plane. One or more antennas for the handheld electronic device may be formed from the ground plane and one or more associated antenna resonating elements. Transceiver circuitry may be connected to the resonating elements by transmission lines such as coaxial cables. Ferrules may be crimped to the coaxial cables. A bracket with extending members may be crimped over the ferrules to ground the coaxial cables to the housing and other conductive elements in the ground plane. The ground plane may contain an antenna slot. A dock connector and flex circuit may overlap the slot in a way that does not affect the resonant frequency of the slot. Electrical components may be isolated from the antenna using isolation elements such as inductors and resistors.

18 Claims, 38 Drawing Sheets

